



Jetcol® High Speed ■ SUBLIMATION TRANSFER PAPER ■

Jetcol® HIGH SPEED is designed to combine a fast drying time of the ink with an exceptional high transfer yield. Our Jetcol® HIGH SPEED allows for high-speed printing, whilst offering all the outstanding properties within the Jetcol® portfolio. No additional external dryers are needed for the paper.



Worldwide
availability



Premium
quality



Cost efficient
solution



Your sustainable
partner

Jetcol® High Speed ■ SPECIFICATION



JETCOL® HIGH SPEED

- Excellent drying speed
- High rub resistance of printed paper
- Available in wide range of specifications



GSM	95
Ink coverage	
Transfer yield	
Dry speed	

GENERAL

- The outside of the roll is the coated side / printing side.
- Suitable for industrial and plotter printers.

SUSTAINABILITY



Thanks to our in-house water recovery management we are able to re-use 95% of the water we use for paper production.

RECOMMENDED PRINT ROOM SETTINGS

- Ideal printing room temperature is 23°C and 40-60% relative humidity.
- For good dimensional stability, flatness of paper and faster ink drying, maintain ideal printing room climatic conditions

RECOMMENDED TRANSFER SETTINGS



Temperature: 195-205°C
Time: 25-40 seconds

Ideal settings might vary depending on the process, print environment and textiles.

AVAILABILITY

TYPE	WIDTH		LENGTH		DIAMETER	
	MM	INCH	M	FT	MM	INCH
plotter	420	16,5	50	164	140	5,5
plotter	1620	64	135	443	165	6,5
plotter	1900	75	135	443	165	6,5
plotter	2570	101	135	443	165	6,5
plotter	3200	126	135	443	165	6,5
mini-jumbo	1620	64	1000	3280	400	16

Standard Core is 76 mm / 3 inch.

For plotter rolls 420 mm / 16,5 inch core is 50 mm / 2 inch.

Other sizes or special dimensions are available on request, contact the licensed agent or a Coldenhove sales representative for more information

SHELF LIFE

This product is covered with a 1,5 year guarantee after receiving the product, under above mentioned storage and handling conditions. Preserve or note down the lot numbers on the roll. In case of quality issues refer to those numbers.

STORAGE AND HANDLING

- Store material in original packaging only.
- Avoid exposure to direct sunlight and extreme weather conditions.
- Place the roll to in the printing room at least 24 hours prior to printing. Handle the rolls with care while transporting within your premises. Damaged rolls may not be usable.
- For heavier paper rolls, mainly jumbo, we suggest not to leave them hanging on the printer over a prolonged period, as this may in some cases bend the core bar.



We invest in saving and re-using energy. Residual heat is used for heating offices and the swimming pool in Eerbeek.



All our papers contain high quality fibers and can be recycled up to 7 times.

CERTIFICATIONS



The mark of responsible forestry



Scan the QR code for more info or visit www.coldenhove.com

IMPORTANT: Printers and heat presses vary in accuracy. We have tested our products with numerous printers and pressed with excellent results. Nonetheless, we recommend that you test the paper in your equipment to ensure the best results. Coldenhove's maximum obligation shall be to replace any paper that has proven to be defective.