



Jetcol® HTR3500 ■ SUBLIMATION TRANSFER PAPER ■

We developed the Jetcol® HTR3500 to solve a quality challenge: 'rivering' also called 'arching' and 'treeing'. Rivering takes place when the gasses that build up during the sublimation process seep out to the edges of the textile. We designed our Jetcol® HTR3500 paper with a special coating that prevents gas build up between the paper and the textile. The result is a very sharp image.



Worldwide
availability



Premium
quality



Cost efficient
solution



Your sustainable
partner

Jetcol® HTR3500 ■ SPECIFICATION



SUSTAINABILITY



Thanks to our in-house water recovery management we are able to re-use 95% of the water we use for paper production.



We invest in saving and re-using energy. Residual heat is used for heating offices and the swimming pool in Eerbeek.



All our papers contain high quality fibers and can be recycled up to 7 times.

CERTIFICATIONS



The mark of responsible forestry



JETCOL® HTR 3500

- Suitable for closely knitted textiles
- Anti-riveting
- Easy handling on printer and calander



GSM	105
Ink coverage	
Transfer yield	
Dry speed	

GENERAL

- The outside of the roll is the coated side / printing side.
- Suitable for industrial and plotter printers.

RECOMMENDED PRINT ROOM SETTINGS

- Ideal printing room temperature is 23°C and 40-60% relative humidity.
- For good dimensional stability, flatness of paper and faster ink drying, maintain ideal printing room climatic conditions.

RECOMMENDED TRANSFER SETTINGS



Temperature: 195-205°C
Time: 25-40 seconds

Ideal settings might vary depending on the process, print environment and textiles.

AVAILABILITY

TYPE	WIDTH		LENGTH		DIAMETER	
	MM	INCH	M	FT	MM	INCH
plotter	1620	64	100	328	165	6,5
plotter	1900	75	100	328	165	6,5
plotter	2390	94	100	328	165	6,5
plotter	2570	101	100	328	165	6,5
plotter	2640	104	100	328	165	6,5
plotter	3200	126	140	459	190	7,5
mini jumbo	3200	126	500	1640	350	14
jumbo	1620	64	4450	14600	900	35,5
jumbo	3200	126	2700	8858	900	35,5

Standard Core is 76 mm / 3 inches.

Other sizes or special dimensions are available on request, contact the licensed agent or Coldenhove sales representative for more information.

SHELF LIFE

This product is covered with a 1,5 year guarantee after receiving the product, under above mentioned storage and handling conditions. Preserve or note down the lot numbers on the roll. In case of quality issues refer to those numbers.

STORAGE AND HANDLING

- Store material in original packaging only.
- Avoid exposure to direct sunlight and extreme weather conditions.
- Place the roll to in the printing room at least 24 hours prior to printing. Handle the rolls with care while transporting within your premises. Damaged rolls may not be usable.
- For heavier paper rolls, mainly jumbo, we suggest not to leave them hanging on the printer over a prolonged period, as this may in some cases bend the core bar.



Scan the QR code for more info or visit www.coldenhove.com

IMPORTANT: Printers and heat presses vary in accuracy. We have tested our products with numerous printers and pressed with excellent results. Nonetheless, we recommend that you test the paper in your equipment to ensure the best results. Coldenhove's maximum obligation shall be to replace any paper that has proven to be defective.