



Jetcol® TA ■ SUBLIMATION TRANSFER PAPER ■

**DISCOVER OUR JETCOL® TA, THERMAL
ADHESIVE SUBLIMATION TRANSFER PAPERS.**

The properties of high quality sportswear such as stretch ability and colour brilliance differ in each and every application. Coldenhove has developed a family of sticky sublimation papers with various grammages for printing on sportswear.

With this family, you are ready to print high standards quality sportswear in every print job.



Worldwide
availability



Premium
quality



Cost efficient
solution



Your sustainable
partner

Jetcol® TA ■ SPECIFICATION

JETCOL® TA FAMILY

After we introduced Jetcol® TA into the market, it became a great success. This paper is equipped with a special coating, that sticks to the fabric while transferring the image. This special feature reduces the chances of ghosting, without any risk of leaving residue on the textile. We continued developing

special papers also for the Industrial printers to ensure print houses can grow their quantity, output, efficiency, and improve productivity performances. We help you choose the right paper to achieve an optimal result during every print job.

	GSM	Ink coverage	Transfer yield	Dry speed	Adhesive force	USPs
JETCOL® TA	85/105					- Medium adhesive paper - Suitable for various elastic fabrics - Avoids ghosting and shadow lines

GENERAL

- The outside of the roll is the coated side / printing side.
- Suitable for plotter printers using water based sublimation inks.

RECOMMENDED PRINT ROOM SETTINGS

- Ideal printing room temperature is 23°C and 50% relative humidity.
- Maintaining ideal printing room climatic conditions for good dimensional stability, flatness of paper and faster ink drying.

RECOMMENDED TRANSFER SETTINGS



Temperature: 195-205°C
Time: 25-40 seconds

Ideal settings might vary depending on the process, print environment and textiles.

STORAGE AND HANDLING

- Store material in original packaging only.
- Avoid exposure to direct sunlight and extreme weather conditions.
- Place the roll to be printed in printing room at least 24 hours prior to printing.
Handle the rolls with care while transporting within your premises. Damaged rolls may not be usable.
- For heavier paper rolls, mainly jumbo, we suggest not to leave them hanging on the printer over a prolonged period, this may in some cases bend the core bar.

SHELF LIFE

This product is covered with a guarantee of 1 year after receiving the product under above mentioned storage and handling conditions. Preserve or note down the lot numbers on the roll. In case of quality issues refer to those numbers.



Scan the QR code for instructional video or go to the link www.coldenhove.com

IMPORTANT: Printers and heat presses vary in accuracy. We have tested our products with numerous printers and pressed with excellent results. Nonetheless, we recommend that you test the paper in your equipment to ensure the best results. Coldenhove's maximum obligation shall be to replace any paper that has proven to be defective.



SUSTAINABILITY



Thanks to our in-house water recovery management we are able to re-use 95% of the water we use for paper production.



We invest in saving and re-using energy. Currently all energy required by the factory comes out of energy released during the production of paper. Residual heat is used for heating offices and the swimming pool in Eerbeek.



All our papers contain high quality fibers and can be recycled up to 7 times.

CERTIFICATIONS



The mark of responsible forestry

