



COLDENHOVE

Xtreme® Sign

Sublimation Transfer Paper

INNOVATION MEETS PERFORMANCE.



Worldwide
availability



Premium
quality



Cost efficient
solution



Your sustainable
partner

Xtreme® Sign ■ SPECIFICATION

XTREME® SIGN

- Superior print sharpness
- Outstanding color consistency
- Solves rivering challenges
- Fast drying



GSM	70
Ink coverage	
Transfer yield	
Dry speed	

GENERAL

- The outside of the roll is the coated side / printing side.
- Suitable for (semi) industrial printers.

RECOMMENDED PRINT ROOM SETTINGS

- Ideal printing room temperature is 23°C and 40-60% relative humidity.
- Following the recommended climate conditions will promote dimensional stability, flatness of paper and faster ink drying.

RECOMMENDED TRANSFER SETTINGS



Temperature: 195 – 205°C
Time: 30 - 45 seconds

Ideal settings might vary depending on the process, print environment and textiles.

XTREME® SIGN APPLICATIONS

Signage is a highly visual market that defines itself by vibrant colors and extreme detail. Designed to meet the demands of the signage market, Xtreme® Sign sublimation paper transfers seamlessly for consistent and vibrant graphics in every print job! Xtreme® Sign provides high drying speed with anti-rivering that will help increase production while achieving consistent quality with sharp, flawless prints.

Success in the personalization market also requires versatile production and quick deliveries, Xtreme® Sign is interchangeable between hard and soft goods, expanding printing possibilities to a wider range of substrates and boosting production turn over.

AVAILABILITY

TYPE	WIDTH		LENGTH		DIAMETER	
	MM	INCH	M	FT	MM	INCH
plotter	3200	126	235	459	190	7,5
mini jumbo	3200	126	1125	3690	380	15
jumbo	3200	126	4050	13287	700	27,5

Standard Core is 76 mm / 3 inches.

Other sizes or special dimensions are available on request, contact the licensed agent or Coldenhove sales representative for more information.

SHELF LIFE	With proper storage and handling conditions, this product is covered under a 1.5 year guarantee upon receipt. Each roll is labeled with a lot number. When reporting issues please refer to the lot number.
STORAGE AND HANDLING:	• Store material in original packaging only. • Avoid exposure to direct sunlight and extreme weather conditions. • Place the roll to in the printing room at least 24 hours prior to printing. Handle the rolls with care while transporting within your premises. Damaged rolls may not be usable.



Scan the QR code for more info or visit www.coldenhove.com/xtreme-sign/

IMPORTANT: Printers and heat presses vary in accuracy. We have tested our products with numerous printers and presses with excellent results. Nonetheless, we recommend that you test the paper in your equipment to ensure the best results. Coldenhove's maximum obligation shall be to replace any paper that has proven to be defective.

Xtreme®

SUSTAINABILITY



Thanks to our in-house water recovery management we are able to re-use 95% of the water we use for paper production.



We invest in saving and re-using energy. Residual heat is used for heating offices in the winter, and the heating the public swimming pool of Eerbeek in the summer. .



All our papers contain high quality fibers and can be recycled up to 7 times.

CERTIFICATIONS



The mark of responsible forestry

