



COLDENHOVE

Xtreme® Sports

Sublimation Transfer Paper

INNOVATION MEETS PERFORMANCE.



Worldwide
availability



Premium
quality



Cost efficient
solution



Your sustainable
partner

Xtreme® Sports ■ SPECIFICATION



SUSTAINABILITY



Thanks to our in-house water recovery management we are able to re-use 95% of the water we use for paper production.



We invest in saving and re-using energy. Residual heat is used for heating offices and the swimming pool in Eerbeek.



All our papers contain high quality fibers and can be recycled up to 7 times.

CERTIFICATIONS



The mark of responsible forestry



XTREME® SPORTS

	GSM	Ink coverage	Transfer yield	Dry speed	Market	USPs
XTREME® SPORTS	100					- High print stability - High ink loads - Exceptional drying speed
NEW XTREME® SPORTS	70					- High drying speed - Excellent print quality and sharp details - Optimised transfer yield

GENERAL

- The outside of the roll is the coated side / printing side.
- Suitable for plotter printers using water based sublimation inks.
- *Suitable for Kyocera inks and printheads.*

RECOMMENDED PRINT ROOM SETTINGS

- Ideal printing room temperature is 23°C and 40-60% relative humidity.
- For good dimensional stability, flatness of paper and faster ink drying, maintain ideal printing room climatic conditions

RECOMMENDED TRANSFER SETTINGS



Temperature: 195-205°C
Time: 30-45 seconds

Ideal settings might vary depending on the process, print environment and textiles.

STORAGE AND HANDLING

- Store material in original packaging only.
 - Avoid exposure to direct sunlight and extreme weather conditions.
 - Place the roll to be printed in printing room at least 24 hours prior to printing.
- Handle the rolls with care while transporting within your premises. Damaged rolls may not be usable.
- For heavier paper rolls, mainly jumbo, we suggest not to leave them hanging on the printer over a prolonged period, this may in some cases bend the core bar.

SHELF LIFE

This product is covered with a guarantee of 1,5 year after receiving the product under above mentioned storage and handling conditions. Preserve or note down the lot numbers on the roll. In case of quality issues refer to those numbers.

AVAILABILITY

TYPE	WIDTH		LENGTH		DIAMETER	
	MM	INCH	M	FT	MM	INCH
Plotter	162	64	110	360	165	6,5
Plotter	162	64	300	984	240	9,4
Mini jumbo	162	64	825	3706	380	15
Mini jumbo	180	64	1200	3937	450	18
Mini jumbo	162	64	1200	3937	450	18
Mini jumbo	180	71	1500	4921	500	19,5
Jumbo	162	64	4800	15 748	900	35,5

Standard Core is 76 mm / 3 inches.

Other sizes or special dimensions are available on request, contact the licensed agent or Coldenhove sales representative for more information.



Scan the QR code for more info or visit www.coldenhove.com

IMPORTANT: Printers and heat presses vary in accuracy. We have tested our products with numerous printers and presses with excellent results. Nonetheless, we recommend that you test the paper in your equipment to ensure the best results. Coldenhove's maximum obligation shall be to replace any paper that has proven to be defective.