



Xtreme® Light ■ SUBLIMATION TRANSFER PAPER ■

**DISCOVER OUR TWO VERSIONS OF XTREME® LIGHT,
THE PERFORMANCE OF A PREMIUM SUBLIMATION PAPER, IN 45 AND 40 GSM.**

Xtreme® Light is a low weight paper designed for the fast industrial printers producing beautifully printed fashion garments.

Due to the lower weight this paper is especially suitable for printing companies who deliver all over the world and aim to reduce their environmental impact.



Worldwide
availability



Premium
quality



Cost efficient
solution



Your sustainable
partner

Xtreme® Light ■ SPECIFICATION

XTREME® LIGHT

	GSM	Ink coverage	Transfer yield	Dry speed	Market	USPs
XTREME® LIGHT	45					■ Easy handle – more print stability ■ High transfer yield ■ Low transportation costs of printed paper
NEW XTREME® LIGHT	40					■ Faster transfer time ■ More paper on a roll ■ High transfer yield

GENERAL

- The outside of the roll is the coated side / printing side.
- Suitable for plotter printers using water based sublimation inks.

RECOMMENDED PRINT ROOM SETTINGS

- Ideal printing room temperature is 23°C and 50% relative humidity.
- Maintaining ideal printing room climatic conditions for good dimensional stability, flatness of paper and faster ink drying.

RECOMMENDED TRANSFER SETTINGS



Temperature: 195-205°C
Time: 25-40 seconds

Ideal settings might vary depending on the process, print environment and textiles.

STORAGE AND HANDLING

- Store material in original packaging only.
- Avoid exposure to direct sunlight and extreme weather conditions.
- Place the roll to be printed in printing room at least 24 hours prior to printing.
Handle the rolls with care while transporting within your premises. Damaged rolls may not be usable.
- For heavier paper rolls, mainly jumbo, we suggest not to leave them hanging on the printer over a prolonged period, this may in some cases bend the core bar.

SHELF LIFE

This product is covered with a guarantee of 1,5 year after receiving the product under above mentioned storage and handling conditions. Preserve or note down the lot numbers on the roll. In case of quality issues refer to those numbers.

AVAILABILITY

TYPE	WIDTH		LENGTH		DIAMETER	
	MM	INCH	M	FT	MM	INCH
Xtreme Light® 45 gsm						
mini jumbo	1620	64	2000	6562	380	15
mini jumbo	1620	64	3300	10827	500	20
jumbo	1620	64	10700	35105	900	35,5
Xtreme Light® 40 gsm						
mini jumbo	1620	64	2400	7874	380	15
mini jumbo	1620	64	4300	14108	500	20
jumbo	1620	64	8650	28379	700	27,5
jumbo	1620	64	14100	46260	900	35,5

Standard Core is 76 mm / 3 inches.

Other sizes or special dimensions are available on request. Anyone interested can contact the licensed agent or a Coldenhove sales representative.



Scan the QR code for instructional video or go to the link www.coldenhove.com

IMPORTANT: Printers and heat presses vary in accuracy. We have tested our products with numerous printers and pressed with excellent results. Nonetheless, we recommend that you test the paper in your equipment to ensure the best results. Coldenhove's maximum obligation shall be to replace any paper that has proven to be defective.

SUSTAINABILITY



Thanks to our in-house water recovery management we are able to re-use 95% of the water we use for paper production.



We invest in saving and re-using energy. Currently all energy required by the factory comes out of energy released during the production of paper. Residual heat is used for heating offices and the swimming pool in Eerbeek.



All our papers contain high quality fibers and can be recycled up to 7 times.

CERTIFICATIONS



The mark of responsible forestry

